



»» Blue M

1500 °C Crucible Furnace

1500°C Crucible Furnace

Our 1500° Crucible Furnace is designed for easy maintenance and convenient operation. The efficient design allows for dependability and durability. Insulation aids in heating uniformity for precise, uniform temperature control which is required for today's high-temperature processes. This unit automatically sets the PID values for your thermal process.



► Features

- Vertical, single-ended silicon carbide heating elements
- High-temperature grade insulation
- Tight-fitting insulating vestibule plug
- Platinum/ Platinum 13% rhodium thermocouple lead wire and plug
- Self-tuning temperature controller
- Front panel configuration of thermocouple input, instrument temperature range, and other control parameters
- Programmable heat-up and setpoint temperature
- Indicates setpoint and process temperatures simultaneously
- Temperature
 - 1500°C (2732°F) Maximum
- Crucible Sizes
 - 5" (Top Vestibule ID) x 8" (Heated Depth) -
 - 12" (Top Vestibule ID) x 18" (Heated Depth)

Model	Top Vestibule ID inches (cm)	Heated Depth inches (cm)	Wattage	Overall Dim. inches (cm)	Use w/ Control Type	Shipping Weight lbs.
56623	5 (12.7)	8 (20.3)	6,140	30x33x33 (76.2x83.8x83.8)	58125	650
56953	9 (22.9)	12 (30)	6,800	33x35x35 (83.8x 88.9x88.9)	58125	700
56253	12 (30)	12 (30)	12,000	34x38x38 (86.4x96.5x96.5)	58155	710
56283	12 (30)	18 (45.7)	14,800	38x39x39 (96.5x99x99)	58155	800

1500°C Crucible Controllers		
Model	58125	58155
Preset TC Input	Type R	Type R
Preset Control Range	1-1500°C	1-1500°C
Maximum Current	60 Amps	90 Amps
Voltage	208/240	208/240
Hertz	50/60	50/60
Overall Size (HxWxD in inches)	10 x 14 x 19 (25.4 x 35.6 x 48.3)	17 x 17 x 21 (43.2 x 43.2 x 53.3)
Shipping Weight	30 lbs.	50 lbs.

All specifications are subject to change without notice.

Options:

- Pots
- Inert atmosphere retorts
- Combustible gas safety system
- Computer communications software
- Programmable control (Option P)
 - Offers flexibility of ramping to multiple setpoint levels and holding for variable time periods at those levels
- Excess temperature protection (Option B)
 - Provides positive protection of both furnace and load in the event of failure in the primary control circuit.
 - Redundant circuit includes separate analog setting instrument with manual reset pushbutton, magnetic contractor and independent thermocouple.
- Digital communication kits
 - Allow modification and interrogation of all instrument control and configuration parameters from a remote computer.
 - Available to interface with RS-232 or RS-422/485 communication ports
- Programmer controller (Option P4)
 - Provides four 16-segment programs of ramps (up or down) and dwells (timed holds)



Gruenberg, Blue M, Tenney

Mailing Address: P.O. Box 150 | White Deer, PA 17887-0150 | USA

Phone: (570) 538-7200 | Fax: (570) 538-7380

Physical Address: 2821 Old Route 15 | New Columbia, PA 17856-9396

info@thermalproductsolutions.com

Specifications and Product Information are subject to change without notice.

THERMAL PRODUCT SOLUTIONS

»»Blue M »»Gruenberg »»Lindberg/MPH »»Tenney